

ATL's Poly Tank Holds <u>Full</u> Strength HCI ACID!

#### Since 2014 Acid Tank Leasing, LLC.

Has been offering the oilfield's first series of mobile tanks designed exclusively for acid storage. We offer our steel tanks with the patented octagon design for HCI storage up to 20% and our poly tanks for up to 36% HCI concentration. Our steel-lined tanks have 50% fewer welds than a frac tank and are internally coated with a proprietary liner, which is the most advanced of its kind on the market today.

Home Office: 2710 East Chestnut Enid, Oklahoma 73701 580.540.0014

### Don't put HCI into a tank designed for H2O


Frac tanks used in today's oilfield often share a common problem, they leak externally over time. Not surprising when you think about putting hydrochloric acid into a frac tank designed to store water. In addition to being a serious health and environmental risk, leaking frac tanks cost millions of dollars in litigation, cleanup costs and fines from the EPA, OSHA, and other federal and state regulated agencies.

### SAFETY DESIGNED QUALITY DEFINED

# The ATL tank is a true acid tank designed to:

ACID TANK LEAS

- Minimize the Costs of Leaks and Spills
- Enhance Safety
- Reduce Environmental Liability/ Increase Profitablity



Patented Rinse System

## www.acidtankleasing.com



Available Nationwide • Steel - Lined Tank 380 Bbls/480 Bbls • Poly Tank 390 Bbls











Home Office: 2710 East Chestnut Enid, Oklahoma 73701 580.540.0014



### **Specifications**

- Steel Tanks: 380 or 480 Bbls; Max HCI Concentration 20%
- Poly Tanks 390 Bbls; Max HCI Concentration 36% (Full Strength)
- 1/4" Steel Plate, Smooth Wall Construction
- 3/8" Steel Plate Front & Rear Walls
- Floor Sloped to Center for Complete Drainage
- Acid Resistant Liner Interior Welds
- Reinforced Acid Resistant Liner Interior Welds
- Support Legs Slope Tank 2" Back to Front
- 16" Tank Ground Clearance
- Manway with Viton<sup>™</sup> Gasket
- Fill Line: 3" Acid Resistant Butterfly Valve with 2" camlock Connection
- Rinse Line: 3" Butterfly Valve 2"camlock nail hook up
- 6" Flanged Manifold with (4) 4" butterfly valves, 4" female Threaded flange
- Floor Drain Connected to Manifold (Drain tank completely)
- Electronic Gauging for better accuracy
- Scrubber System to reduce HCL fumes by over 98%
- OSHA Compliant Stairway
- 5th Wheel King Pin Hitch
- Gauging Charts on Catwalk area
- Safety Signage
- DOT Light Package
- Scrubber system reduces the HCL fumes down to less than 2 PPM
- Improved Safety with 360° View of Acid Tanks
- Reduced Environmental Liability with 50% Fewer Welds than a Frac Tank
- Patented Internal Rinse System
- Longer Service Life than a Retro-Fitted Frac Tank
- Lowered Tank Neutralization Costs
- Able to be DOT Compliant in all 50 States

# www.acidtankleasing.com